

## Data sheet

# PEANUT Y



## GENERAL

Art. no.:	HSG-022-2,5-1	E-class number:	40-02-01-03
EAN:	4030281183440	Customs no.:	84798997
Standard:	BASED ON EN 354:2010 EN 360:2002 RFU CNB/P/11.060 RFU CNB/P/11.085		

## Data sheet

### PEANUT Y

The compact connecting device PEANUT Y with FS90 ALU karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the fall height is extremely low. The all-rounder carabiner with an opening width of 60 mm is suitable for almost all structures and can be opened easily. The lanyard is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and therefore also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 2.5 m long arms, the PEANUT Y is ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

#### FEATURES

Fall indicator

---

Suitable for edges: yes

---

Max. service life: 10 Years

---

Max. number of persons: 1

---

Rated load: 135 KG

---

Patent

---

Temperature: from 45 °C to -35 °C

---

Suspension element: BAND

---

Area of application:

---

Construction / Roofer / Carpenter, Scaffolding

#### DIMENSIONS

---

Size: 2,5m

---

Weight: 2,85 kg

---

## HARDWARE

Carabiner on anchoring point side:

FS 90 ALU

---

Carabiner on belt side: STAK TRI

---

## MATERIAL

Material:

Polyester, Polyamide, Aluminium

---