

## Data sheet

# PEANUT Y



## GENERAL

Art. no.:	HSG-022-2,5-7	E-class number:	40-02-01-03
EAN:	4030281294856	Customs no.:	84798997
Standard:	BASED ON EN 354:2010 EN 360:2002 RFU CNB/P/11.060 RFU CNB/P/11.085		

## Data sheet

### PEANUT Y

The compact connecting device PEANUT Y with the RESISTOR karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the drop height is extremely low. The RESTISTOR is extremely robust and handy and is particularly suitable for quick hooking into the structure. The fastener is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and therefore also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 2.5 m long arms, the PEANUT Y is ideal for securing in scaffolding. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap has been released and provides additional safety.

#### FEATURES

Fall indicator

---

Suitable for edges:           yes

---

Max. service life:           10 Years

---

Max. number of persons: 1

---

Rated load:                   135 KG

---

Patent

---

Temperature:                from 45 °C to -35 °C

---

Suspension element:       BAND

---

Area of application:

---

Scaffolding, Wind Energy / Offshore Industry

#### DIMENSIONS

---

Size:                           2,5m

---

Weight:                       2,23 kg

---

## HARDWARE

Carabiner on anchoring point side:

RESISTOR

---

Carabiner on belt side: STAK TRI AL

---

## MATERIAL

Material:

Polyester, Polyamide, Aluminium

---