

Data sheet

HK PLUS





GENERAL

| Art. no.: | HSG-050-06 |
|-----------|----------------------------------|
| EAN: | 4030281247319 |
| Standard: | CNB/P/11.060:2005 EN 360:2002 |

| E-class number: | 40-02-01-03 |
|-----------------|-------------|
| Customs no.: | 84798997 |



Data sheet

HK PLUS

HK PLUS fall-arrest blocks stand for a high degree of freedom of movement along with a short fall distance, which makes these reliable fall arresters the ideal companions for many jobs at height.

The automatic rope retraction ensures that only the rope length actually required is extended. This means that the arrest distance is always as short as possible, whether the system is anchored overhead or applied horizontally.

Further advantages at a glance:

- Maximum vertical working weight up to 140kg
- Edge suitability: HK PLUS devices are suitable for edges without using additional energy absorbers, which makes them appropriate for horizontal use as well
- Fall indicator: Carabiner has an integrated color symbol to display a previous fall and indicates that the device needs to be checked
- Resistant materials: Synthetic housing integrates cutting-edge technology for an extended service life

FEATURES

Fall indicator

| Suitable for edges: | yes |
|-------------------------|----------------------|
| Max. service life: | 10 Years |
| Max. number of persons: | 1 |
| Rated load: | 140 KG |
| Temperature: | from 45 °C to -35 °C |
| Suspension element: | ST4,8 |

DIMENSIONS

| Size: | 6m |
|---------|---------|
| Weight: | 3,49 kg |

MATERIAL

Material:

Acrylnitril-Butadien-Styrol, Steel