

Data sheet

ERGOGRIP SK12



GENERAL

| | | | |
|-----------|---------------|-----------------|-------------|
| Art. no.: | L-0030-2 | E-class number: | 40-02-01-90 |
| EAN: | 4030281052852 | Customs no.: | 56090000 |
| Standard: | EN 358:2018 | | |

Data sheet

ERGOGRIP SK12

Work positioning ropes are for getting into the right working position. The core-sheathed ropes used by SKYLOTEC can withstand extreme edge loads, are resistant to abrasion, remain soft in damp conditions and feature a long service life. It is an extremely simple matter to adjust the Ergogrip range with self-locking carabiners with one hand.

FEATURES

| | |
|-------------------------|---|
| Diameter: | 12,00 mm |
| Hand-washing: | 40 °C |
| Max. service life: | 10 Years |
| Max. number of persons: | 1 |
| Temperature: | from 45 °C to -35 °C |
| Suspension element: | KM12 |
| Area of application: | Power Supplies / -Transmission / Telecommunications, Rope Access / Rigging |

DIMENSIONS

| | |
|---------|---------|
| Size: | 2m |
| Weight: | 0,95 kg |

HARDWARE

| | |
|----------------------|------------|
| Carabiner on device: | OVALOY TRI |
| Carabiner on rope: | OVALOY TRI |

MATERIAL

Material: Polyamide, Aluminium

Rope material: Polyamide
