

Data sheet

BFD SK12



GENERAL

| | | | |
|-----------|----------------------------|-----------------|-------------|
| Art. no.: | L-0097-2 | E-class number: | 40-02-01-04 |
| EAN: | 4030281002147 | Customs no.: | 56090000 |
| Standard: | EN 354:2010 EN 355:2002 | | |

Data sheet

BFD SK12

FEATURES

Fall indicator

| | |
|-----------|----------|
| Diameter: | 12,00 mm |
|-----------|----------|

| | |
|---------------|-------|
| Hand-washing: | 40 °C |
|---------------|-------|

| | |
|--------------------|----------|
| Max. service life: | 10 Years |
|--------------------|----------|

| | |
|-------------------------|---|
| Max. number of persons: | 1 |
|-------------------------|---|

| | |
|--------------|----------------------|
| Temperature: | from 45 °C to -35 °C |
|--------------|----------------------|

| | |
|---------------------|------|
| Suspension element: | KM12 |
|---------------------|------|

DIMENSIONS

| | |
|-------|----|
| Size: | 2m |
|-------|----|

| | |
|---------|---------|
| Weight: | 1,17 kg |
|---------|---------|

HARDWARE

Carabiner on anchoring point side:

FS 90 ALU

| | |
|-------------------------|----------|
| Carabiner on belt side: | STAK TRI |
|-------------------------|----------|

MATERIAL

Material: Polyamide, Aluminium

Rope material: Polyamide
