

## Data sheet

# LOOP SEP 40 kN



### GENERAL

Art. no.:	L-0397-2	E-class number:	40-02-01-04
EAN:	4030281100287	Customs no.:	63079098
Standard:	EN 354:2010 EN 795-B:2012		

## Data sheet

### LOOP SEP 40 kN

LOOP SEP was specially developed for working at sharp edges. The tensile force of 40 kN and the flexible casing made from special cutproof fibres make the loop practically indestructible. The fixing is stitched conically so that the loop does not get caught at this critical point.

#### FEATURES

Breaking load, major axis:

40,00 kN

---

Diameter:	30,00 mm
-----------	----------

---

Hand-washing:	40 °C
---------------	-------

---

Suitable for edges:	yes
---------------------	-----

---

Max. service life:	10 Years
--------------------	----------

---

Max. number of persons:	1
-------------------------	---

---

Patent	
--------	--

---

Temperature:	from 45 °C to -35 °C
--------------	----------------------

---

Area of application:

Fire brigade / Rescue / Special Forces, Rope Access / Rigging

---

#### DIMENSIONS

---

Size:	2m
-------	----

---

Weight:	0,85 kg
---------	---------

---

## HARDWARE

Carabiner on belt side: KOBRA TW

---

## MATERIAL

Material: Polyester, Steel

---