


Data sheet

SKYSAFE PRO TIE BACK





GENERAL

Art. no.:	L-0575-1,8	E-class number:	40-02-01-04
EAN:	4030281181569	Customs no.:	56090000
Standard:	EN 354:2010		
	EN 355:2002 EN 795:2012		
	RFU PPE-R/11.063 V1:2018		
	RFU PPE-R/11.074		
	V1:2018	_	



Data sheet

SKYSAFE PRO TIE BACK

ONE4ALL – Revolutionary, patented energy absorber with the large weight range from 50kg to 140kg that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m. The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO also meets the most relevant international standards in a SINGLE product.

Available in four versions with different carabiner combinations: I-web, Y-web, I-web tie-back, Y-web tie-back.

GENERAL

Internat. standard: ANSI Z359.13-6/12FTFF:2013, AS/NZS 1891.1:2007, MEETS CSA Z259.11-05-E6:2010

FEATURES

Fall indicator			
Breaking load, major axis:			
22,00 kN			
Hand-washing:	40 °C		
Suitable for edges:	yes		
Max. service life:	10 Years		
Max. number of persons: 1			
Rated load:	140 KG		
Patent			
Rescue Loop:	yes		
Temperature:	from 45 °C to -35 °C		
Suspension element:	BAND		



DIMENSIONS

Size:	1,8m
Weight:	1,29 kg

HARDWARE

Carabiner on anchoring point side: FS 64 ALU Carabiner on belt side: KOBRA AL TRI

MATERIAL

Material: Polyester, Polyamide, Aluminium Webbing material: Polyester, Polyamide