

Data sheet

SKYSAFE PRO ADJUSTABLE I



GENERAL

Art. no.:	L-0641-1,8	E-class number:	40-02-01-04
EAN:	4030281229384	Customs no.:	56090000
Standard:	EN 354:2010 EN 355:2002 EN 795:2012 RFU PPE-R/11.063 V1:2018 RFU PPE-R/11.074 V1:2018		

Data sheet

SKYSAFE PRO ADJUSTABLE I

50 - 140 kg WITHIN the standard!

The popular SKYSAFE PRO, now also available in a length-adjustable version! Revolutionary, patented absorber system, which guarantees a max. impact of under 6 kN and a max. fall arrest distance of 1.75 m, even for a broad weight range of 50 - 140 kg. This makes SKYLOTEC the only manufacturer to fulfil the EN 355 standard with an increased test weight of 140 kg and it has also been tested for use on lifting platforms.

Another feature of the absorber, the final impact resistance of 22 kN before AND after a fall is exceptional. The SKYSAFE PRO also meets the most relevant international standards in a SINGLE product.

The SKYSAFE PRO adjustable version completes the SKYLOTEC range of I-web, Y-web, I-web tie-back, Y-web tie-back with a length-adjustable version, which always ensures the optimum distance for your work.

GENERAL

Internat. standard:
ANSI Z359.13-6/12FTFF:2013

FEATURES

Fall indicator

Diameter: 25,00 mm

Hand-washing: 40 °C

Suitable for edges: yes

Max. service life: 10 Years

Max. number of persons: 1

Rated load: 140 KG

Temperature: from 45 °C to -35 °C

Suspension element: BAND

DIMENSIONS

Size: 1,2m - 1,8m

Weight: 1,60 kg

HARDWARE

Carabiner on anchoring point side:

FS 90 ST ANSI

Carabiner on belt side: KOBRA TRI

MATERIAL

Material:

Polyester, Polyamide, Steel

Webbing material: Polyester, Polyamide
