

Data sheet

Set Lory PRO



GENERAL

| | |
|-----------|--|
| Art. no.: | L-0693-3 |
| EAN: | 4030281287278 |
| Standard: | EN 12841-C:2006 EN 15151-1:2012 EN 341-2A:2011 |

| | |
|-----------------|-------------|
| E-class number: | 40-02-01-90 |
| Customs no.: | 84798997 |

Data sheet

Set Lory PRO

Model: OVALOY TRI/KOBRA TRI

LORY is a robust descender and belay device. Its various application areas make the Lory your reliable companion for rope access and rescue (abseiling up to 225 kg load). LORY is used for work positioning, as a restraining device at roofs or slab edges, as a temporary anchor or for fall arrest in flexible cable systems. With LORY, the belaying person can easily feed and take rope. When using the device correctly, it blocks automatically in case of a fall. The LORY PRO model with its unimpeded movement of the cam is the ideal device for industrial purposes. It is equipped with a descent handle that ensures secured and controlled abseiling. The double-stop function blocks if the handle is pulled overly in panic and provides extra safety.

EN 341: max./min. rated load: 30 - 180 kg;
max. descent height: 190 m; rope diameter: 11 mm

EN 12841-C: max. rated load: 225 kg; rope diameter: 10-12 mm

EN 795: rope diameter: 10.5 / 11 mm

ANSI Z359.4-2013

FEATURES

| | |
|----------------------|-----------------------|
| Diameter: | 10,50 mm |
| Max. service life: | 10 Years |
| Temperature: | from 60 °C to -20 °C |
| Suspension element: | KM10,5 |
| Area of application: | Rope Access / Rigging |

DIMENSIONS

| | |
|---------|---------|
| Size: | 3m |
| Weight: | 1,09 kg |

HARDWARE

| | |
|----------------------|------------|
| Carabiner on device: | OVALOY TRI |
| Carabiner on rope: | OVALOY TRI |

MATERIAL

Material:
Polyamide, Aluminium, Steel