

## Data sheet

# SKYSAFE PRO



## GENERAL

Art. no.:	L-0748-2	E-class number:	40-02-01-04
EAN:	4030281283294	Customs no.:	56090000
Standard:	EN 354:2010 EN 355:2002 EN 795:2012 RFU PPE-R/11.063 V1:2018 RFU PPE-R/11.074 V1:2018		

## Data sheet

### SKYSAFE PRO

ONE4ALL - Revolutionary, patented energy absorber with the large weight range from 50kg to 140kg that always withstands a maximum impact of less than 6 kN at a maximum absorber length of 1.75m. The final impact resistance of 22 kN, also in the absorber, before AND after a fall is exceptional as well. SKYSAFE PRO also meets the most relevant international standards in a SINGLE product.

Available in four versions with different carabiner combinations: I-web, Y-web, I-web tie-back, Y-web tie-back.

#### FEATURES

Fall indicator

---

Breaking load, major axis:

22,00 kN

---

Hand-washing: 40 °C

---

Suitable for edges: yes

---

Max. service life: 10 Years

---

Max. number of persons: 1

---

Rated load: 140 KG

---

Patent

---

Rescue Loop: yes

---

Temperature: from 45 °C to -35 °C

---

Suspension element: BAND

---

Area of application:

Construction / Roofer / Carpenter

---

## DIMENSIONS

Size: 2m

Weight: 1,22 kg

## HARDWARE

Carabiner on anchoring point side:

FS 90 ALU

Carabiner on belt side: KOBRA TRI

## MATERIAL

Material:

Polyester, Polyamide, Aluminium

Webbing material: Polyester, Polyamide