

## Data sheet

# LORY X



## GENERAL

|           |   |                 |             |
|-----------|---|-----------------|-------------|
| Art. no.: | L-0761-20   | E-class number: | 40-02-01-90 |
| EAN:      | 4030281295075                                     | Customs no.:    | 84798997    |
| Standard: | CEN/TS 16415:2013<br>EN 358:2018<br>EN 795-B:2012 |                 |             |

## Data sheet

### LORY X

LORY X (model with carabiners STEEL D TRI / FS 64 ALU) is a work positioner that can be adjusted under loads. The device has a handle for setting it to an optimal working position while in motion. An integrated panic function prevents unintended lurching rope movement if the lever is opened too far. The silver button in the middle of the device can no longer be opened by pressing which prevents unintentional opening during use. All that's needed to exchange the rope when worn or if needed is an Allan wrench size 2. The rope thickness is 11 mm. LORY X can also be used as a backup safety device or lanyard.

- Adjustable work positioning rope when under loads
- Anti-panic function with strong lever
- Rope can be exchanged using an Allan wrench

#### FEATURES

|                     |                      |
|---------------------|----------------------|
| Diameter:           | 11,00 mm             |
| Max. service life:  | 10 Years             |
| Rated load:         | 150 KG               |
| Temperature:        | from 60 °C to -20 °C |
| Suspension element: | KM11                 |

#### DIMENSIONS

|         |         |
|---------|---------|
| Size:   | 20m     |
| Weight: | 3,59 kg |

#### HARDWARE

|                      |             |
|----------------------|-------------|
| Carabiner on device: | STEEL D TRI |
| Carabiner on rope:   | FS 65 Alu   |

#### MATERIAL

|           |                       |
|-----------|-----------------------|
| Material: | Polyamide, ALU, Steel |
|-----------|-----------------------|