

Data sheet

SUPER STATIC 11.0



GENERAL

Art. no.:	R-079-WE-200
EAN:	4030281117469
Standard:	EN 1891-A:1998

E-class number:	40-02-90-06
Customs no.:	56075030

Data sheet

SUPER STATIC 11.0

The static rope Super Static is designed for heavy loads when working at heights as well as for rescue and winch operations. Expansion and sheath slip are low. The abrasion resistance of the sheath, on the other hand, is so high that it is even suitable for climbing clamps. At the same time, the Super Static is also flexible enough to be used for rescue operations with long abseiling distances.

FEATURES

Number of standard falls:

10

Diameter:	11,00 mm
-----------	----------

Hand-washing:	40 °C
---------------	-------

Max. tensile force (EN 1891):	
-------------------------------	--

30,00 kN

Max. service life:	10 Years
--------------------	----------

Max. number of persons:	1
-------------------------	---

Rope type:	STAT
------------	------

Static elongation:	3,00 %
--------------------	--------

Temperature:	from 55 °C to -35 °C
--------------	----------------------

Area of application:	Rope Access / Rigging
----------------------	-----------------------

DIMENSIONS

Size:	200m
Weight:	15,20 kg

MATERIAL

Material:	Polyamide
-----------	-----------