

Data sheet

Set Lory PRO



GENERAL

Art. no.:	L-0699-3	E-class number:	40-02-01-90
EAN:	4030281287322	Customs no.:	84798997
Standard:	EN 12841-C:2006 EN 15151-1:2012 EN 341-2A:2011		

Data sheet

Set Lory PRO

Model: DOUBLE TRI/ATTACK

LORY is a robust descender and belay device. Its various application areas make the Lory your reliable companion for rope access and rescue (abseiling up to 225 kg load). LORY is used for work positioning, as a restraining device at roofs or slab edges, as a temporary anchor or for fall arrest in flexible cable systems. With LORY, the belaying person can easily feed and take rope. When using the device correctly, it blocks automatically in case of a fall. The LORY PRO model with its unimpeded movement of the cam is the ideal device for industrial purposes. It is equipped with a descent handle that ensures secured and controlled abseiling. The double-stop function blocks if the handle is pulled overly in panic and provides extra safety.

EN 341: max./min. rated load: 30 - 180 kg;
max. descent height: 190 m; rope diameter: 11 mm

EN 12841-C: max. rated load: 225 kg; rope diameter: 10-12 mm

EN 795: rope diameter: 10.5 / 11 mm

ANSI Z359.4-2013

FEATURES

Diameter:	10,50 mm
Max. service life:	10 Years
Temperature:	from 60 °C to -20 °C
Suspension element:	KM10,5

DIMENSIONS

Size:	3m
Weight:	0,95 kg

HARDWARE

Carabiner on device:	DOUBLE-O TRI
Carabiner on rope:	DOUBLE-O TRI

MATERIAL

Material:
Polyamide, Aluminium, Steel