

## Datenblatt

**SPARK****ALLGEMEIN**

|                        |               |
|------------------------|---------------|
| Art.Nr:                | A-056         |
| GTIN:                  | 4030281010913 |
| E-class number:        | 40-02-01-06   |
| Customs tariff number: | 84798997      |

|               |  |
|---------------|--|
| Standards:    | EN 12841-C:2006, EN 15151-1:2012, EN 341-2A:2011 |
| Net weight:   | 0.51 kg  |
| Gross weight: | 0.51   |

## Datenblatt

# SPARK

SPARK is designed for permanent use in the toughest conditions. The product combines the advantages of the best descenders for industrial and rescue use. SPARK is characterised in particular by its design without anti-panic function, which enables fast, precise and uninterrupted abseiling. Intuitive and simple rope handling, while the carabiner on the harness can remain connected to the device, the well thought-out ergonomics and the precise operation of the lever allow for the best handling. Thanks to the sophisticated rope guide inside the device, the rope is protected against twisting and kinking as well as heavy wear.

- Fast, precise, uninterrupted abseiling without anti-panic-function
- Outstanding handling thanks to compact, ergonomic design and intuitive rope guide
- Durable and robust: 100% metal without vulnerable plastic parts

### MERKMALE

|                                   |                         |
|-----------------------------------|-------------------------|
| Application areas:                | Various                 |
| Colour:                           | Black, synthetic_rubber |
| Lifting function:                 | No                      |
| Max. Abseil speed:                | 2.00 m/s                |
| Maximum compatible rope diameter: | 12.00 mm                |
| Maximum load 1 person:            | 141.00 kg               |
| Maximum load 2 persons:           | 250.00 kg               |
| Maximum lifetime:                 | 30 yyyy                 |
| Maximum lifetime before 2018:     | 0 yyyy                  |
| Maximum number of persons:        | 2                       |
| Maximum load:                     | 250.00 kg               |
| Maximum temperature:              | 60 °C                   |
| Minimum compatible rope diameter: | 9.00 mm                 |
| Minimum temperature:              | -30 °C                  |
| Panic function:                   | Yes                     |
| Rescue function:                  | Yes                     |

### MATERIAL

|           |                  |
|-----------|------------------|
| Material: | Aluminium, Steel |
|-----------|------------------|