

Data sheet

PEANUT Y



GENERAL

Art. no.:	HSG-022-1,8-7	E-class number:	40-02-01-03
EAN:	4030281294849	Customs no.:	84798997
Standard:	BASED ON EN 354:2010 DIN 19427:2017 EN 360:2002 RFU CNB/P/11.060 RFU CNB/P/11.085		

Data sheet

PEANUT Y

The compact connecting device PEANUT Y with the RESISTOR karabiner convinces with its self-retracting arms, which do not restrict the working radius and ensure that the drop height is extremely low. The RESTISTOR is extremely robust and handy and is particularly suitable for quick hooking into the structure. The fastener is perfectly suited for continuous, mutual securing - even at lower heights. The PEANUT Y is edge-suitable and therefore also serves for horizontal securing. The product contains the One-4-All damper and is therefore suitable for a very wide range of user weights from 50 to 135 kilograms. Due to the 1.8 m long arms, the PEANUT Y is ideal for securing in aerial work platforms. The fastener is available in a variety of karabiner variants (aluminium, steel, etc.). A red indicator shows when the strap fall arrester has been released and provides additional safety.

FEATURES

Fall indicator

Suitable for edges: yes

Max. service life: 10 Years

Max. number of persons: 1

Rated load: 135 KG

Patent

Temperature: from 45 °C to -35 °C

Suspension element: BAND

Area of application:

Facade / Window Cleaning, High Rack

DIMENSIONS

Size: 1,8m

Weight: 2,21 kg

HARDWARE

Carabiner on anchoring point side:

RESISTOR

Carabiner on belt side: STAK TRI AL

MATERIAL

Material:

Polyester, Polyamide, Aluminium
